

20 WALL MOUNTED 1x1 INVERTER

MUPR Series

MUNDCLIMA®

- Inverter Type compressor
- 40% energy saving
- ANION function
- It can operate up -10°C
- Biological filter against odours
- Included low temperature kit
- Control of condensed water
- Treatment against corrosion
- Long life hydrophilic aluminium
- Automatic restart
- Infrared remote control
- R407C Ecological gas



TECHNICAL SPECIFICATIONS

Model		MUPR-09 HN	MUPR-11 HN
Part No.		—	CL 20 086
Gas		R-407C	
COOLING capacity	W	2,500 (900~3,000)	3,200 (1,000~3,500)
	Btu/h	9,000	11,000
	kcal/h	2,150	2,750
HEATING capacity	W	3,000 (1,100~3,500)	4,000 (1.350~4,500)
	Btu/h	10,400	12,000
	kcal/h	2,600	3,000
Power consumption Cooling	W	1,000	1,250
Power consumption Heating	W	1,100	1,450
Dehumidification capacity	l/h	1.2	1.2
Air flow	m ³ /h	440	530
Power supply		230 V - 50 Hz - 1 Phase	
Noise level indoor unit (*)	dB(A)	35	36
Noise level outdoor unit (**)	dB(A)	47 (52)	49 (55)
Dim. indoor unit (Width x Height x Depth)	mm	830 x 285 x 189	
Dim. outdoor unit (Width x Height x Depth)	mm	848 x 540 x 320	
Weight indoor/outdoor unit	kg	11 / 40	
Gas pipe diameter	inch	3/8"	1/2"
Líquid pipe diameter	inch	1/4"	
Cooling line max. length***	m	10	
Maximum distance	m	5	

(*) Noise level to maximum speed (1 m distance); (**) Noise level at 3 m distance (1 m as per CE)

(***) For other length, please see additional charging gas table.

- **Energy saving: the speed of compressor and the refrigerant volume are automatically controlled according to the environment.**