

20 WALL MOUNTED SPLITS

MUP Series "Big Capacity"

MUNDOCLIMA®

- Long reach Air flow
- High efficiency exchanger
- Intelligent defrosting system
- Easily washable filters
- Biological filter against odours (optional)
- Treatment against corrosion
- Long life hydrophilic aluminium
- Automatic restart
- Particularly quiet
- Infrared remote control
- Programmable operation
- R-407C "Ecological gas"



TECHNICAL SPECIFICATIONS

Model		MUP-18 CN	MUP-21 CN	MUP-24 CN	MUP-18 HN	MUP-21 HN	MUP-24 HN
Part No. (R-407C)		CL 20 126	CL 20 127	CL 20 128	CL 20 136	CL 20 137	CL 20 138
Gas		R-407C			R-407C		
COOLING capacity	W	5,000	6,000	7,000	5,000	6,000	7,000
	Btu/h	17,500	21,000	24,000	17,200	21,000	24,000
	kcal/h	4,300	5,200	6,000	4,300	5,200	6,000
HEATING capacity	W	—	—	—	6,200	7,000	7,500
	Btu/h	—	—	—	21,300	24,000	25,800
	kcal/h	—	—	—	5,300	6,000	6,450
Power requirement during Cooling	W	2,400	2,600	3,250	2,400	2,600	3,250
Power requirement during Heating	W	—	—	—	2,650	2,600	3,200
Dehumidification capacity	l/h	2.0	2.4	2.8	2.0	2.4	2.8
Air flow	m ³ /h	720	720	1,080	720	720	1,080
Power supply	V-Hz-Ph	230 - 50 - 1			230 - 50 - 1		
Noise level indoor unit*	dB(A)	46	48	50	46	48	50
Noise level outdoor unit**	dB(A)	58	59	59	58	59	59
Indoor unit Ø (Width x Height x Depth)	mm	907 x 290 x 195		1220 x 360 x 206	907 x 290 x 195		1220 x 360 x 206
Outdoor unit Ø (Width x Height x Depth)	mm	950 x 710 x 410		950 x 840 x 412	950 x 710 x 410		950 x 840 x 412
Weight indoor/outdoor unit	kg	12 / 59	12 / 59	24 / 72	12 / 59	12 / 59	24 / 72
Gas pipe diameter	inch	1/2"		5/8"	1/2"		5/8"
Liquid pipe diameter	inch	1/4"		3/8"	1/4"		3/8"
Cooling line max. length***	m	10		20	10		20
Maximum distance	m	5		15	5		15

(*) Noise level to maximum speed (1 m distance); (**) Noise level at 3 m distance (1 m as per CE)

(***) For other length, please see additional charging gas table.