

20 WALL MOUNTED SPLITS

"luxury" MUP Series

MUNDOCLIMA®

- High energetic efficiency
- Biological filter against odours (optional)
- Included low temperature kit
- Control of condensed water
- Treatment against corrosion
- Long life hydrophilic aluminium
- Automatic restart
- Particularly quiet
- Programmable operation
- Infrared remote control
- R-407C "Ecological gas"



TECHNICAL SPECIFICATIONS

Model		MUP-07 CN	MUP-09 CN	MUP-12 CN	MUP-16 CN	MUP-07 HN	MUP-09 HN	MUP-12 HN	MUP-16 HN
Part No. (R-407C)		CL 20 121	CL 20 122	CL 20 123	CL 20 124	CL 20 131	CL 20 132	CL 20 133	CL 20 134
Gas		R-407C				R-407C			
COOLING capacity	W	2,000	2,500	3,500	4,500	2,000	2,500	3,500	4,500
	Btu/h	7,000	9,000	12,000	15,500	7,000	9,000	12,000	15,500
	kcal/h	1,750	2,150	3,000	3,900	1,750	2,150	3,000	3,900
HEATING capacity	W	—	—	—	—	2,300	3,000	3,800	5,200
	Btu/h	—	—	—	—	8,000	9,600	13,200	17,900
	kcal/h	—	—	—	—	2,000	2,400	3,300	4,500
Power requeriment during Cooling	W	940	1,200	1,620	2,000	940	1,200	1,620	2,000
Power requeriment during Heating	W	—	—	—	—	1,050	1,080	1,820	2,200
Dehumidification capacity	l/h	0.8	1.2	1.6	2	0.8	1.2	1.6	2
Air flow	m ³ /h	420	420	520	660	420	420	520	660
Power supply		230 V - 50 Hz - 1 Ph				230 V - 50 Hz - 1 Ph			
Noise level indoor unit (*)	dB(A)	34	34	38	43	34	34	38	43
Noise level outdoor unit (**)	dB(A)	43 (52)	43 (54)	45 (57)	46 (57)	43 (52)	43 (54)	45 (57)	46 (57)
Dim. indoor ut. (WidthxHeightxDepth)	mm	830 x 285 x 189				830 x 285 x 189			
Dim. outdoor ut. (WidthxHeightxDepth)	mm	848 x 540 x 320				848 x 540 x 320			
Weight indoor/outdoor unit	kg	11 / 32			11 / 59	11 / 32			11 / 59
Gas pipe diameter	inch	3/8"		1/2"		3/8"		1/2"	
Liquid pipe diameter	inch	1/4"				1/4"			
Cooling line max. length***	m	10				10			
Maximun distance	m	5				5			

(*) Noise level to maximum speed (1 m distance); (**) Noise level at 3 m distance (1 m as per CE)

(***) For other length, please see additional charging gas table.