

20 WALL MOUNTED SPLITS 2x1 MUP Series

MUNDOCLIMA[®]

- High energetic efficiency
- Anti odour bio filter (optional)
- Equipped with a low temperature kit
- Control of condensed water
- Treatment against corrosion
- Long life hydrophilic aluminium
- Automatic restart
- Extremely quiet
- Programmable operation
- Infrared remote control
- Independent operation: one unit cools while the other heats



TECHNICAL SPECIFICATIONS:

Model			MUP-12X2HG
Part No.			CL 20 157
COOLING capacity	W		3.500 x 2
	Btu/h		12.000 x 2
	Kcal/h		3.000 x 2
HEATING capacity	W		3.600 x 2
	Btu/h		13.000 x 2
	Kcal/h		3.100 x 2
Power consumption	Cooling	W	2.325
	Heating	W	2.111
Dehumidification capacity		l/h	1,2 x 2
Air flow		m ³ /h	630 x 2
EER / C.O.P.		w/w	3,01/3,41
Volt-Frecuency		V-Hz-Ph	230 - 50 - 1
Energy efficiency			B/B
Outdoor unit compressor			Mitsubishi RN135VHEMC
Noise level	Indoor unit	dB(A)	38/34/29
	Outdoor unit	dB(A)	66
Dimensions (Width x height x Depth)	Indoor unit	mm	845 x 275 x 180
	Outdoor unit	mm	950 x 420 x 700
Weight	Indoor unit	kg	10
	Outdoor unit	kg	65
Gas pre-charge		m	4
Extra charge		g/m	30
Gas pipe diameter		inch	1/2" x 2
Liquid pipe diameter		inch	1/4" x 2
Cooling line max. length		mts.	20
Maximum distance		mts.	10