

06 AIR CURTAINS FOR COMMERCIAL DOORS UP TO 2.2 m



OPTIMA

- Self-supporting casing construction made of galvanised plated steel, painted epoxy-polyester structural white colour RAL 9016 as standard. Other colours are available on request.
- Low noise twisted cross-flow fans driven by a 2-speed external rotor motor.
- Micro-perforated inlet grille with filter functions and easy service. It does not need prefilter.
- "E" type includes electrical shielded element, 2 power stages with power switches included. "A" type is without heating, air only.
- Linear blow-out jets with airfoil profiled anodized aluminium vents.
- Control panel and infrared remote control IR included. 20 m of telephone cable with fast connectors type RJ45 (Plug & Play).
- Two or more units can be joined connected by means of a connecting ring RNG 20/30.



Code	Model	Nominal airflow m ³ /h	Electrical heating capacity (kW)		Stages		Sound level dB(A)	Weight Kg
			1x230V	3x400V	Heat	Ventilation		
EC 06 551	OPT 1000 A	850/1350	-	-	-	2	41/50	17.5
EC 06 553	OPT 1000 E	850/1350	-	4/6	2	2	41/50	20.5
EC 06 554	OPT 1000 E230	850/1350	3.8/5.6	-	2	2	41/50	20.5
EC 06 555	OPT 1500 A	1250/2050	-	-	-	2	43/52	25.5
EC 06 557	OPT 1500 E	1250/2050	-	6/9	2	2	43/52	27.5
EC 06 558	OPT 1500 E230-6	1250/2050	3.8/5.6	-	2	2	43/52	27.5
EC 06 559	OPT 1500 E230-9	1250/2050	6/9	-	2	2	43/52	27.5
EC 06 560	OPT 2000 A	1700/2700	-	-	-	2	46/55	33
EC 06 562	OPT 2000 E	1700/2700	-	5.6/11.3	2	2	46/55	42
EC 06 563	OPT 2000 E230	1700/2700	5.6/11.3	-	2	2	46/55	42

DIMENSIONS:

