


WINDOW AIR CONDITIONERS MUVR-C6 Series



ONLY COOLING

- New refrigerant R32.
- Rotative compressor DC inverter.
- Compact design.
- Reduced consumption.
- Easy installation.
- 3 speed fan.
- Timer function.
- Digital display.



Remote control included



Easy-to-dismantle panel



Air renovation



Movable chassis



High air flow rate

TECHNICAL SPECIFICATIONS

MODEL			MUVR-09-C6 (V3)	MUVR-12-C6 (V3)
Code			CL20380	CL20381
Cooling	Nominal capacity	kW	2.78	3.51
	Nominal rating Peer	kW	0.85	1.1
	Nominal intensity	A	3.9	5.1
	Pdesignc	kW	2.8	3.5
	EERd	W/W	3.27	3.20
	SEER	W/W	5.10	5.10
	Energy labeling		A	A
	Electricity Consumption Qsd	kWh/year	194	237
Power consumption in thermostat-off mode Pto		W	15	15
Standby power consumption Psb		W	1	1
Sound pressure level	Indoor Unit (High / Medium / Low)	dB(A)	51.3 / 49.8 / 48.5	52.4 / 51.6 / 50.7
	Outdoor Unit (High)	dB(A)	60	58.5
LWA sound power level	Indoor	dB(A)	56.5	56
	Outdoor	dB(A)	64	64
Power supply		V-Hz-Ph	220-240V~ 50Hz, 1Ph	220-240V~ 50Hz, 1Ph
Max. intensity		A	7	8
Max. consumption		kW	1.29	1.43
Air flow rate	Indoor ut. (High / Medium / Low)	m ³ /h	448 / 391 / 332	420 / 366 / 310
	Outdoor ut. (High)	m ³ /h	780	680
Refrigerant	Type		R32	R32
	Amount	kg	0.39	0.48
	GWP Global Warming Potential	kg CO ₂	675	675
Design pressure		MPa	1.7 - 4.8	1.7 - 4.8
Dimensions (W x D x H)		mm	560 x 670 x 400	560 x 670 x 400
Weight		kg	46.1	47.8
Remote control model			RG51	RG51
Temperature Operation	Indoor	°C	17 to 35	17 to 35
	Outdoor	°C	18 to 43	18 to 43

Warning: 1. Data and specifications are subject to changes without previous notice.
2. The values of noise level match with values obtained in the anechoic chamber.