

## WINDOW AIR CONDITIONERS MUVR-C9 Series




Remote control included  
(Code. CL98640)

**NEW!**

### ONLY COOLING

- New refrigerant R32.
- DC inverter rotary compressor.
- Compact design.
- Reduced consumption.
- Easy installation.
- 3 speed fan.
- Timer function.
- Digital display.



### TECHNICAL SPECIFICATIONS

MODELO			MUVR-09-C9	MUVR-12-C9
Code			CL 20 382	CL 20 383
Cooling	Nominal capacity	kW	2.7	3.65
	Nominal consumption PEER	kW	0.782	1.03
	Nominal intensity	A	3.9	4.6
	Pdesignc (design load)	kW	2.8	3.7
	EERd	W/W	3.45	3.54
	SEER	W/W	5.2	5.4
	Energy labeling		A	A
	Electricity Consumption QSD	kWh/year	182	240
Power consumption in thermostat-off mode PTO		W	0.00324	0.00326
Standby power consumption PSB		W	0.00065	0.00069
Sound pressure level	Indoor Unit (High / Medium / Low)	dB(A)	50 / 48 / 46	50 / 48 / 46
	Outdoor unit (High)	dB(A)	56 / 54 / 52	58 / 56 / 54
LWA sound power level	Interior	dB(A)	59	59
	Exterior	dB(A)	65	65
Power supply		V-Hz-Ph	220-240 V~ 50 Hz, 1Ph	220-240 V~ 50 Hz, 1Ph
Max. intensity		A	5.5	6.5
Max. consumption		kW	1.1	1.3
Air flow rate	Indoor (High / Medium / Low)	m³/h	400 / 360 / 320	480 / 430 / 380
	Outdoor (High)	m³/h	800	1200
Refrigerant	Type / PCA		R32 / 675	R32 / 675
	Amount	kg/tCO <sub>2</sub> eq	0.51 / 0.34	0.63 / 0.43
Dimensions (W x D x H)		mm	560 x 710 x 375	660 x 700 x 428
Weight		kg	43	50
Operation temp.	Interior	°C	16 to 30	16 to 30
	Exterior	°C	16 to 43	16 to 43

Note: 1. Data and specifications are subject to changes without previous notice.

2. The values of noise level match with the values obtained in the semi-anechoic chamber.