

DOUBLE DUCT AIR CONDITIONER MUSER-H12 Serie

MUNDCLIMA®

- DC Inverter Compressor.
- Built-in control panel and remote control.
- Installation on the ground.
- Ultracompact design.
- Low sound level.
- Easy to install: only two 180 mm holes.
- Built-in Wi-Fi control.



Remote control included



TECHNICAL SPECIFICATIONS

MODEL			MUSER-12-H12
Code			CL20101
EAN Code			8432953053550
Cooling	Nominal capacity (min. ~ max.)	kW	3,50 (1,00 ~ 4,10)
	Nominal consumption PEER	kW	1,35
	EERd	W/W	2,6
	Energy labeling		A
	Electricity Consumption QSD	kWh/60min	1,35
Heating	Nominal capacity (min. ~ max.)	kW	2,93 (0,80 ~ 4,10)
	Nominal consumption PEER	kW	0,815
	COPd	W/W	3,6
	Energy Efficiency Class		A+
	Electricity Consumption QSD	kWh/60min	0,815
Power consumption in thermostat-off mode PTO		W	0
Standby power consumption PSB		W	1,3
Sound power level LWA		dB(A)	60
Power supply		V-Hz-F	220-240 V~ 50 Hz, 1 N
Max. current		A	6
Air flow	Interior	m³/h	520
	Exterior	m³/h	600
Diameter of the exterior tubes		mm²	180
Refrigerant	Type / PCA		R290 / 3
	Quantity	kg / TCO ₂ eq	0,29 / 0,0
Dimensions (W x D x H)		mm	1000 x 205 x 590
Weight		kg	43,5
Temperature while operating	Indoor (Cooling / Heating)	°C	18 ~ 35 / -3 ~ 28
	Outdoor (Cooling / Heating)	°C	-5 ~ 43 / -7 ~ 43

Notes:

* The values of sound level match with the values obtained in a semi-anechoic chamber.

** All the data and specifications can be changed without previous notice.