

CONDENSATE PUMPS EASY AQUA



It's one of the smallest condensate removal pumps in the market. It has been designed in order to fit where others cannot!

FEATURES:

- Extra-slim.
- High performance.
- Plug and play.



Max. flow rate: 15 l/h.



Max. rec. height: 12 m.



19 dB (A).

SUITABILITY:

- Up to 16 kW / 54 000 BTU/h.
- Mini wall split system; duct units; floor-ceiling devices.
- Perfect for installing directly inside the device.

SPECIFICATIONS:

- Max. flow rate: 15 l/h at 0 m.
- Max. Height: 12 m.
- Max suction height: 2 m.
- Sound level at 1 m: 19 dB (A).
- Power supply: 230 VAC / 50/60 Hz.
- Class: Class II device.
- Max. outlet: 16 kW / 54,000 BTU/h.
- Max. water temperature: 40 °C / 104 °F.
- Discharge tube: Ø 6 mm.
- IP Protection: IPX5
- Safety switch: 3 A NC.
- Thermal protection: Yes.
- Completely encapsulated: Yes.
- Self-priming: Yes.

BOX CONTENT:

- Pump body.
- Vinyl tube (Ø 6 mm).
- In-line tank: sensor cover and cable, filter, float, tank.
- 1.5 m vinyl tube (Ø 6 mm).
- 20 cm long vinyl tube (Ø 4 mm ID).
- Inlet tube.
- Power supply cable.
- 2x self-adhesive Velcro strips.
- 2x adapters.
- 4x cable ties 110 x 5 mm.
- 2x cable ties 110 x 3 mm.
- Installation manual.



Code AS 06 806

