

AIR CURTAIN TO BUILD-IN GUARDIAN BUILD-IN Series

Height from 2.5 to 4 m

- Suspended ceiling assembly.
- Innovative design.
- Up to 4 m high.
- RAL 9003 White.
- Control included.



Control (included)




External probe (EC 06 190)



Door contact (EC 06 191)



Timer (EC 06 192)



Code	Model	Recom. min. Height m	Length mm	kW
AIR ONLY CURTAINS				
EC 06 180	GR1000 A	4	1,125	—
EC 06 181	GR1500 A	4	1,650	—
EC 06 182	GR2000 A	4	2,177	—
CURTAINS WITH ELECTRIC BATTERY				
EC 06 183	GR1000 E	4	1,125	9/12
EC 06 184	GR1500 E	4	1,650	12/18
EC 06 185	GR2000 E	4	2,177	18/24
CURTAINS WITH WATER BATTERY				
EC 06 186	GR1000 W	4	1,125	9/12
EC 06 187	GR1500 W	4	1,650	12/18
EC 06 188	GR2000 W	4	2,177	18/24

TECHNICAL FEATURES

Model	ONLY AIR			WITH ELECTRIC BATTERY			WITH WATER BATTERY			
	GR1000A	GR1500A	GR2000A	GR1000E	GR1500E	GR2000E	GR1000W	GR1500W	GR2000E	
Code	EC 06 180	EC 06 181	EC 06 182	EC 06 183	EC 06 184	EC 06 185	EC 06 186	EC 06 187	EC 06 188	
Power supply	V	230	230	230	400	400	400	230	230	230
Heating power	kW				9/12 ¹	12/18 ¹	18/24 ¹	9/12 ²	12/18 ²	18/24 ²
Speeds	Nº	3	3	3	3	3	3	3	3	
Air flow rate	m³/h	1150/1440/1800	1730/2268/2700	2300/2880/3600	1150/1440/1800	1730/2268/2700	1150/1440/1800	1150/1440/1800	1730/2268/2700	1150/1440/1800
Output speed	m/s	6.4 / 8 / 10	6.4 / 8.4 / 10	6.4 / 8 / 10	6.4 / 8 / 10	6.4 / 8.4 / 10	6.4 / 8 / 10	6.4 / 8 / 10	6.4 / 8.4 / 10	6.4 / 8 / 10
Intensity (factory)	A	1.36	1.97	2.8	13.8	18.4	27.7	13.8	18.5	27.8
Min / max. intensity	A	1.36	1.97	2.8	18	27	36.2	1.36	1.97	2.8
Sound level	dB (A)	52 / 59	52 / 59	52 / 59	52 / 59	52 / 59	52 / 59	52 / 59	52 / 59	52 / 59
Weight	kg	32	48.5	60	34.5	52	64.5	38.5	58	72
Length	mm	1,125	1,650	2,177	1,125	1,650	2,177	1,125	1,650	2,177
High / Bottom	mm	273 / 457	273 / 457	273 / 457	273 / 457	273 / 457	273 / 457	273 / 457	273 / 457	273 / 457
Max. height	m	4	4	4	4	4	4	4	4	4
Control		included	included	included	included	included	included	included	included	included
WHITE COLOR	RAL	9003	9003	9003	9003	9003	9003	9003	9003	9003

¹ Factory settings/maximum settings selectable by customer.

² Average kW with constant water flow rate 82 / 72 °C.