

# INDUSTRIAL AIR CURTAINS

## MU-GC Series


**Height: 5 to 7.5 m**
**FEATURES**

- Can be installed horizontally or vertically.  
It includes anchors that allow the modular installation of several curtains.
- 3-speed motor.
- Air-only models, with water or electric battery.
- Does not include remote control.



Model	ONLY AIR				WATER BATTERY HEATING				2-ROW WATER BATTERY HEATING				ELECTRIC BATTERY HEATING					
	MU-GC-15-A		MU-GC-20-A		MU-GC-15-W		MU-GC-20-W		MU-GC-15-W2F		MU-GC-20-W2F		MU-GC-15/12-R3		MU-GC-20/20-R3			
Code	EC 06 720		EC 06 721		EC 06 722		EC 06 723		EC 06 724		EC 06 725		EC 06 726		EC 06 727			
Speed	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW		
Air flow rate	m <sup>3</sup> /h		6,500	4,300	8,100	5,100	6,200	4,000	8,200	5,200	5,700	3,500	7,600	4,600	6,300	4,100	8,600	5,400
Sound pressure level <sup>(1)</sup>	dB (A)		60	49	62	51	60	49	62	51	60	49	62	51	60	49	62	51
Nominal capacity Heating <sup>(2)</sup>	kW		-		-		29.5		33.1		55.3		62.8		12.0	9.0	20.0	16.5
Max. consumption	W		640	400	960	600	640	400	960	600	640	400	960	600	12.0	9.0	20.0	16.5
Max. absorbed	A		2.8	2.0	4.2	3.0	2.8	2.0	4.2	3.0	2.8	2.0	4.2	3.0	13.0	17.0	23.0	29.0
Max. horiz. or vertical installation distance <sup>(3)</sup>	m		7.5															
Max. water inlet temperature	°C		-				130				130				-			
Max. working pressure	Mpa		-				1.6				1.6				-			
Connection	inch		-				3/4"				3/4"				-			
Power supply	V / Hz		230 / 50												400 / 50			
Protection degree	IP 54																	
Color	Silver - graphite																	
Dimensions (W x H x D)	mm		1,562 x 639 x 549		2,078 x 639 x 549		1,562 x 639 x 549		2,078 x 639 x 549		1,562 x 639 x 549		2,078 x 639 x 549		1,562 x 639 x 549		2,078 x 639 x 549	
Weight	kg		43		58		47.4		62		51.8		66.4		49.8		67	

**Notes:**
<sup>(1)</sup> Sound pressure level measured at a 3 m distance from the unit, in a room with average sound absorption capacity and a 500 m<sup>3</sup> volume.

<sup>(2)</sup> MU-GC-W/W2F: High speed, water temperature 90 / 70 °C, ambient temperature 10 °C. MU-GC-R3: Ambient temperature 10 °C.

<sup>(3)</sup> Isothermal vertical flow range with speed limit greater than 3 m/s

**- The above design and specifications are subject to change of product improvement without prior notice.**
**DIMENSIONS (mm):**


