DATA SHEET



AIR CURTAINS INOX Series

Height from 2.5 to 3.5 m

FEATURES


- · Stainless steel housing.
- Special design.
- Manual controller.
- Two speeds.
- Ideal for saline environments.


The outer casing made of stainless steel is easy to clean and offers a high resistance against fire

With an unique deflector design, which enables the production of air in all directions, being able to adapt to different environments.

It has a switch for high and low speed.

Provided with an optimized electric machinery, it works safely and effectively.





High performance, high efficiency.

TECHNICAL FEATURES

Model			MU-IN 12	MU-IN 15	MU-IN 18
Code			EC 06 472	EC 06 473	EC 06 474
Flow rate	H (high)	m³/h	1,500	1,900	2,280
	L (low)	m³/h	1,200	1,500	1,800
Speed	H (high)	m/s	16	16	16
	L (low)	m/s	13	13	13
Remote control			NOT	NOT	NOT
Manual control			YES	YES	YES
Consumption	H (high)	W	290	380	450
	L (low)	W	260	350	420
Voltage V-Hz-Ph		220-50-1	220-50-1	220-50-1	
Sound level	H (high)	dB (A)	53	55	57
	L (low)	dB (A)	50	52	55
Net weight kg		18.5	25	30	
Dimensions	Length	mm	1,200	1,500	1,800
	Height	mm	241	241	241
	Depth	mm	215	215	215

*Max recommended installation height: 3.5 meters